



ADJUSTABLE LED LIGHT FIXTURES

Adjustable LED downlighters can be tilted into a range of 30° to achieve a desired lighting effect.

- Rotable up to 358°
- Swivel angle 0 – 30°
- IP44 rating
- color temperature and dimmability upon request
- Application: hotel lobbies, offices, museums, galleries, retail

Perfect directional lighting is then reached by its possibility of rotation up to 358°. All luminaires can also be supplied in dimmable version.

ADJUSTABLE LED LIGHT FIXTURES

DIRECTIONAL LIGHTING



A



B



C

	CATALOGUE NUMBER	POWER CONSUMPTION	LUMINOUS FLUX	BEAM ANGLE	COLOR TEMPERATURE	LIFESPAN	DIMENSIONS
A	DL243540-1	35W	4300lm	60°	4000K	40 000h	Ø224x122mm
A	DL172540-1	25W	2050lm	60°	4000K	40 000h	Ø172x125mm
B	DL184027-1	40W	3800lm	15° / 24° / 36° / 60°	2700K	40 000h	168x168x167mm
B	DL183027-1	30W	3000lm	15° / 24° / 36° / 60°	2700K	40 000h	168x168x167mm
B	DL182527-1	25W	2100lm	15° / 24° / 36° / 60°	2700K	40 000h	168x168x167mm
B	DL182027-1	20W	1800lm	15° / 24° / 36° / 60°	2700K	40 000h	168x168x167mm
C	DR398027-2	2x40W	7600lm	15° / 24° / 36° / 60°	2700K	40 000h	353x169x163mm
C	DR396027-2	2x30W	6000lm	15° / 24° / 36° / 60°	2700K	40 000h	353x169x163mm
C	DR395027-2	2x25W	4200lm	15° / 24° / 36° / 60°	2700K	40 000h	353x169x163mm
C	DR394027-2	2x20W	3600lm	15° / 24° / 36° / 60°	2700K	40 000h	353x169x163mm
	DR581227-3	3x40W	11000lm	15° / 24° / 36° / 60°	2700K	40 000h	537x169x163mm
	DR589027-3	3x30W	9000lm	15° / 24° / 36° / 60°	2700K	40 000h	537x169x163mm
	DR587527-3	3x25W	6300lm	15° / 24° / 36° / 60°	2700K	40 000h	537x169x163mm
	DR586027-3	3x20W	5400lm	15° / 24° / 36° / 60°	2700K	40 000h	537x169x163mm



VOLTAGE **230V**

OPERATING TEMPERATURE **-20°- +40°C**

CRI/Ra **≥80**

IP RATING **IP44**